

MIFARE Plus S 2K Cards

MIFARE Plus S 2K cards—also searched as MIFARE Plus S2K—for installed systems that specify the original S generation. Match the exact chip, UID option and required security level before sample approval.

Specify MIFARE Plus S 2K precisely

Order detail	S 2K selection requirement
Generation	Original MIFARE Plus S; S is not an abbreviation for Plus EV1 or EV2.
Memory	2 kB; confirm the actual offered part rather than identifying memory from the artwork.
UID option	Specify the UID type required by the installed system. The S family includes different UID/NUID variants.
Delivery state	Agree SL0 for personalisation, or the required configured state for issuance.
Reader integration	Specify the required security level, reader firmware and application configuration.
Supply	Confirm the exact available part, quantity and batch before agreeing the order.

The MIFARE Plus family: SE, S, X, EV1 and EV2

MIFARE Plus variant	Memory	Security levels (NXP)	Notes
MIFARE Plus SE	1 kB	SL1, SL3	Entry-level AES upgrade for MIFARE Classic 1K; AES-128; Common Criteria EAL4+
MIFARE Plus S	2 kB / 4 kB	SL1, SL3	Original “standard” Plus; AES-128; now discontinued by NXP
MIFARE Plus X	2 kB / 4 kB	SL1, SL2, SL3	Original “expert” Plus; adds SL2, virtual-card support and proximity check; AES-128; EAL4+
MIFARE Plus EV1	2 kB / 4 kB	SL1, SL3	Second-generation Plus; SL2 not offered; proximity check; EAL5+
MIFARE Plus EV2	2 kB / 4 kB	SL0, SL1, SL3	Current Plus; SL1SL3MixMode, Transaction MAC, Proximity Check, Transaction Timer; AES-128; EAL5+

S 2K, S 4K and later Plus generations

Variant	Purchasing distinction
MIFARE Plus S 2K	The priority model on this page for systems explicitly specifying S 2K. Confirm remaining supply.
MIFARE Plus S 4K	A different memory option in the original S family; the existing product photo shows this version.
MIFARE Plus X	A separate original variant with a different feature set; do not substitute it solely because the memory matches.
MIFARE Plus EV1 / EV2	Later generations. EV2 adds functions such as sector-level migration and Transaction MAC; these are not S 2K specifications.

Ordering

- Free standard samples; customised samples carry a setup fee.
- Standard lead time is 2–3 weeks; for MIFARE Plus S 2K, availability and lead time are confirmed for the offered batch.
- Quote-only pricing—send your quantity for a quotation.
- Printing, numbering and encoding options are available for the selected product and material.

Contact

- Email: info@proudtek.com
- WhatsApp: +86 186 6582 0632
- Web: <https://proudtek.com/product/mifare-plus-card/>